

10.01.08-MKD

## СИЛИКОНСКИ ИЗБРАЗДЕНИ МАЛТЕРИ 2.0 И 2.5

1.

2.0 2.5

2.

- 25 kg: (1001),
- \* (162) 2, 3, 4 5
- (JUMIX !),
- 

3.

		2.0	2.5
(kg/dm <sup>3</sup> )		~1,70	~1,75
= +20 °C, = 65 % ( )		~6	~6
EN ISO 7783-2	μ (-)	<60	<60
	(m) S <sub>d</sub>	<0,12 ( d = 2,0 mm) I ( )	<0,14 ( d = 2,5 mm) I ( )
EN 1062-3 W <sub>24</sub> (kg/m <sup>2</sup> h <sup>0,5</sup> )		<0,06 III ( )	<0,06 III ( )
(1 : 1 : 6) EN 24624 (MPa)		>0,25	>0,25



**4.**

1,00 mm), ( 1,5 MPa . CS II EN 998-1),

7 10

: = +20 °C, ( = 65 %).

		( )
	UNIGRUND ( )	120 . 200 g/m <sup>2</sup>
	JUBOSILCOLOR SILICONE ( )	90 . 100 ml/m <sup>2</sup>
	JUBOSILCOLOR SILICONE: = 1 : 1)	90 . 100 ml/m <sup>2</sup>
	SILICONEPRIMER (SILICONEPRIMER: = 1 : 1)	90 . 100 ml/m <sup>2</sup>
	UNIGRUND ( )	120 . 200 g/m <sup>2</sup>
	VEZAKRILPRIMER	~300 ml/m <sup>2</sup>

JUBOSILCOLOR SILICONE SILICONEPRIMER UNIGRUND,  
 = 65 %) UNIGRUND 12 ( = +20 °C,  
 JUBOSILCOLOR SILICONE SILICONEPRIMER 4 6 VEZAKRILPRIMER 24,

**5.**

( 1 dl ).



s      ‰      (      ,

**6.**

(      )  
 s      ‰  
 +35 °C,      +5 °C  
 (~ 30 km/h)      80 %  
 +35 °C,      +5 °C  
 (~ 30 km/h)      80 %  
 ( = +20 °C,      = 65 %)      (      24      )

~2,8 kg/m <sup>2</sup> (      2.0)
~3,5 kg/m <sup>2</sup> (      2.5)

**7.**

- R 52/53 .
- S 2 .
- S 26 .
- S 28 .
- 29 .
- S 46 .
- 61 .

(      08 01 12).      (      : 17 09 04)

**8.**

2.0      2.5



REVITALCOLOR AG

REVITALCOLOR SILICONE

9.

+5 °C +25 °C,

12

10.

ISO 9001. JUB  
ISO 14001 OHSAS

18001.

2.0 2.5

ETAG 004/2000 JUB Österreichisches Institut für Bautechnik

11.

E2000 JUB  
ISO 7724/1-3 CIE DE2000 . 2,5. TRC JUB d.

o. o.

JUB

25.

(Y)

JUMIX

Oznaka in datum izdaje: TRC-055/12-gru-tor, 21.09.2012



---

**JUB d.o.o.e.l. Skopje**

Bul. Jane Sandanski br. 79/a/3  
1000 Skopje  
Republika Makedonija  
T: +389 2 2454 027  
+389 2 2454 027  
F: +389 2 2455 235  
E: [kiril\\_boskov@jub.com.mk](mailto:kiril_boskov@jub.com.mk)  
[www.jub.eu](http://www.jub.eu)

